

**RANGER™**  
MOBILE ANCHOR

ROAD RANGER

ARREST FALLS.  
ANYWHERE.



**GORBEL®**  
A CLASS ABOVE

## VERSATILE FALL ARREST ANCHOR. ANYWHERE.

The versatile Ranger™ Mobile Anchor line from Gorbel® provides the necessary anchorage point right where you need it, indoors or out. Available in two models, the Ranger is perfect for use when maintaining aircraft, railroad cars, industrial equipment or heavy machinery. This new addition to the Tether Track™ brand of fall protection systems can be easily moved into position and erected. The Ranger's sleek, balanced design allows for easy towing and transport to and around the job site.

Both Ranger models have an adjustable height 2-in. ball coupler that attaches to trucks, or related towing devices. The base model includes integral fork pockets allowing for smooth loading and unloading during transport or for general movement via fork lift. All components are easily accessible at ground level for quick adjustment. Mast extends in a direct path for use in tight environments.

- Easy to position with mast in folded position or fully deployed
- Fully extends to 18, 20, or 22 ft. height to address a wide range of jobs
- Allows single user to move freely within a 30 degree work angle in all directions
- Rugged steel construction and components for superior strength
- Resilient finish to withstand harsh outdoor and indoor environments
- Rated for highway towing up to 65 mph (Road Ranger model)





MAX. HEIGHT 22 FT.

■ PIVOTING D-RING FOR QUICK ATTACHMENT OF SELF-RETRACTING LANYARD

■ BATTERY POWERED WITH ELECTROMECHANICAL ACTUATOR – May be activated with pendant or 915 Hz remote (both included). Allows mast to be smoothly raised and lowered quickly, keeping productivity at high levels.

*Eliminates concerns about leakage of hydraulic fluid.*



■ AUTOMATIC OVER CENTER LOCKING HINGE PROVIDES SAFETY REDUNDANCY

Ranger Mobile Anchors permit workers to maneuver and set-up in areas where periodic maintenance and related activities must be performed on large equipment. Additionally, they are the perfect solution when inspections must be performed on outdoor generators, holding tanks and other large pieces of equipment that have no reliable options for tie-off. Used in conjunction with a full body harness and self-retracting lifeline, Ranger Mobile Anchors provide a complete fall arrest system “on the go.”

■ PIN ADJUSTMENT FOR VARIOUS HEIGHTS (18, 20, 22 FT)

■ AUTOMATIC LOCKING SPRING PIN INDICATES WHEN MAST IS FULLY DEPLOYED

■ ACCESSIBLE BUBBLE AIDS IN LEVELING

■ LARGE/LOCKABLE STORAGE BOX – Allows full access to controls, permits storage of harnesses, self-retracting lanyards, and taglines.

■ HEAVY-DUTY, STEEL OUTRIGGERS WITH LARGE DIAMETER FEET FOR SUPERIOR STABILIZATION

Road Ranger Model

The Ranger base model (not rated for highway towing) features a hinged tow bar and stowaway dolly for easy maneuvering around jobsite.

■ **HINGED TOW BAR** – Conveniently folds out of the way

■ **STOWAWAY DOLLY** – Permits a single user to maneuver the Ranger into position even with the mast fully deployed. Conveniently attaches to bottom of unit when not in use.



Ranger Base Model

Ranger™ Mobile Anchors meet OSHA fall protection codes and ANSI Z359.6 design requirements for fall arrest systems.



GENERAL:	ROAD RANGER™ RATED FOR HIGHWAY TOWING	RANGER™ (BASE) NOT RATED FOR HIGHWAY TOWING
Reach at 18-ft.	8'-6"	8'-6"
Reach at 20-ft.	8'	8'
Reach at 22-ft.	6'-10"	6'-10"
Total Weight:	3,120 lbs.	2,685 lbs.
<b>WHEN IN USE:</b>		
Length when Set-up (excluding reach)	15'	11'
Width with Outriggers Extended	11'-11"	11'
Maximum Work Angle from Anchor Point	30 degrees	30 degrees
Actuating Method	12V Linear Actuator	12V Linear Actuator
Controls	Wired Pendant or 915 Hz Wireless	Wired Pendant or 915 Hz Wireless
Power Source	12V Battery	12V Battery
Charging System	110V, 10 Amp Quick Charger	110V, 10 Amp Quick Charger
Outrigger System	Manual Ratcheting	Manual Ratcheting
Maximum Capacity	310 lbs.	310 lbs.
Total Workers Allowed	1	1
<b>WHEN TOWING:</b>		
Width when Towed	6'-3"	5'-6"
Height when Towed	6'-7"	6'-6"
Length when Towed	16'-2"	15'-3"
Maximum Towing Speed	65 mph	25 mph

**SEE THE RANGER IN ACTION!**

Scan with your smartphone's QR reader to watch video.



**GORBEL**®  
A C L A S S A B O V E



www.gorbel.com

**GORBEL**  
600 Fishers Run  
PO Box 593  
Fishers, NY 14453 USA

T 800.821.0086  
T 585.924.6262  
F 585.924.6273  
E info@gorbel.com